

FLOWSORT **CONVEYOR ROLLERS**

Versatile and reliable solution for every conveyor system



LOW NOISE, HIGH SPEED

Increased speed with reduced noise levels



SMOOTH OPERATION

Smooth running rollers for universal usage



EASY APPLICATION

Reduces downtime during setup



CUSTOMIZABLE




Adaptable for specific operational needs

FLOWSORT ROLLERS

Versatile and reliable solution for every conveyor system

PRODUCTS OVERVIEW



Drive mode	GRAVITY	O-BELT DRIVEN	POLY-V BELT DRIVEN
Tube diameter	40 / 50 / 60 mm	40 / 50 / 60 mm	50 mm
Available length	100 - 1510 mm	100 - 1510 mm	121 - 1510 mm
Tube material	Stainless steel / Zinc plated	Stainless steel / Zinc plated	Stainless steel / Zinc plated
Coating material	SS / Steel ZP / PU / PVC	SS / Steel ZP / PU / PVC	SS / Steel ZP / PU / PVC
Axle diameter	8 mm / 11 mm  / 12 mm	8 mm / 11 mm  / 12 mm	11 mm  / 12 mm
Installation method			
• spring loaded	•	•	•
• external thread	•		
• internal thread	•	•	•
• fixed shaft	•	•	
• flat milling	•		•

To explore additional options or discuss a customized solution, please contact us.

CONTACT US

+31 [0]85-0761339
+39 [0]2-61298711

info@flow-sort.com
info@pbmek.it

www.flow-sort.com
www.pbmek.it